



# ULTRAMATIC EQUIPMENT CO.

Vibratory Finishing Equipment Technology Since 1959

848 S. Westgate Drive · Addison, IL. 60101 · (630) 543-4565  
sales@ultrasonic-equipment.com



Made in  
the USA

## P 8 TUB MACHINE – DIRECT DRIVE SERIES

Ultrasonic **Model P8** Tub Type Vibratory Deburring and Finishing Machine, steel fabricated heavy-duty construction as specified and described below.

**Direct Drive Series** features a Heavy-Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings.

Perfect for all types of jobs from deburring aluminum aircraft parts to cleaning Thread Protectors.

Model	P 8
Total Capacity	8 Cu Ft
Tub Width (After Lining)	18 “
Tub Length (After Lining)	48 “
Machine Length	58 “
Machine Width	38 “
Machine Height	42 “
Shipping Weight	1100 lbs.
Polyurethane Lining	7/8 “
Drive Unit HP / lbs. Force	1.05 / 2470
Input Voltage:	230/460/3/60



### STANDARD FEATURES

- Offset Drive for Superior Finishing Power
- Direct Drive System with Adjustable Weights
- Coil Spring Suspension with Urethane Mounts
- Flo Thru Manifold
- Paint: Black Industrial Enamel / Twilight Gray
- Manual Starter with Overload Protection 230/460-volt 3 phase
- Premium Urethane Cast Lining
- Sound Reduction Tub Cover
- Media Discharge Door with Quick Lock
- Removable Drain with Hose
- Recirculation pump and 7 g tank
- Base with Floor Mounting Pads

For literature, video and additional information please visit [www.ultrasonic-equipment.com](http://www.ultrasonic-equipment.com)

STANDARD FEATURES



VIBRATOR MOTOR

- MORE ENERGY TO TUB DUE TO DIRECT DRIVE DESIGN
- EASY ADJUSTABLE WEIGHTS (COVER REMOVED)
- LUBRICATED FOR LIFE
- 50% LESS HP REQUIRED
- RUNS SUPER QUIET



Manual Starter with  
Overload Protection



Plug Door with  
Quick Lock



Tub Cover Flap



Tank and pump

AVAILABLE OPTIONS

110 VOLT VSDT • VARIABLE SPEED DRIVE WITH TIMER, SOLUTION PUMP RECEPTACLE, CORDED PLUG, STAND MOUNTED	
ST15FS / ST40FS / ST90FS FILTRATION TANKS	REMOVABLE TUB DIVIDER
AUTOMATIC PREMIXING COMPOUND SYSTEM	CASTERS
MEDIA AND COMPOUND STARTER KIT	OTHER OPTIONS AVAILABLE ON REQUEST
230/460 VOLT CONTROL PANEL WITH 0 TO 6 HOUR TIMER (DISCONNECT BY CUSTOMER)	



110v VSDT OPTION includes  
Variable Speed Drive, Timer,  
pump receptacle with Corded Plug



ST15FS Option



AUTOMATIC PREMIXING  
COMPOUND SYSTEM  
(cover removed)



230/460 V CONTROL PANEL  
WITH TIMER OPTION