



**ULTRAMATIC** EQUIPMENT CO.

Vibratory Finishing Equipment Technology Since 1959



## ***P3 SE Vibratory Tub Machine***

Ultramatic P Series machines started the Cell Concept in Vibratory Deburring. Still manufactured here in the USA we are the oldest family owned manufacturer of vibratory finishing equipment around.



DIRECT DRIVE SERIES features a Heavy Duty Vibratory Motor with easily adjustable weights. This unique design feature eliminates belts and pulleys and supplies 100 % power to the Tub. Requires 50% less HP resulting in huge electrical operation cost savings.

Model P3 SE Vibratory Deburring and Finishing Machine includes direct drive , vfd (variable speed) solution tank and pump and Sound Enclosure

### **STANDARD FEATURES**

UNIQUE OFFSET DRIVE FOR SUPERIOR FINISHING RESULTS  
DIRECT DRIVE WITH EASY ADJUSTABLE WEIGHTS  
HINGED SOUND COVER FOAM LINED METAL CABINET  
AC VARIABLE SPEED DRIVE W/ DIGITAL DISPLAY  
110 VOLT SWITCH , PUMP RECEPTACLE W/ CORDED PLUG  
CASTERS WITH LOCK FOR PORTABILITY  
COIL SPRING SUSPENSION WITH URETHANE MOUNTS  
PAINT: TWILIGHT GRAY INDUSTRIAL ENAMEL

CAST POLYURETHANE LINING  
MEDIA DISCHARGE DOOR  
REMOVABLE DRAIN WITH HOSE  
ADJUSTABLE AMPLITUDE  
COMPOUND SPRAY PIPING  
RECIRCULATION PUMP AND TANK  
LUBRICATED FOR LIFE  
ONE YEAR WARRANTY



### **TYPICAL APPLICATIONS**

Deburring fabricated aluminum or steel parts  
Thread protectors  
Deburring aluminum die cast heat sinks  
Degreasing automotive starter/alternator housings  
Polishing boat propellers

Great for Powder and Ceramic Coaters  
Improve surface finish on titanium ball valves  
Deburring machined pinion gears and spline shafts  
Pre-anodize finish on long extruded aluminum parts  
Deburring of bronze water meter housings

VIDEO IS AVAILABLE ON OUR WEBSITE

## STANDARD FEATURES



SPECIFICATIONS	
Tub Length Inside after lining	28.5"
Tub Width Inside after lining	15"
Total Capacity	3 Cu. Ft.
Load Capacity	650 Lbs.
Machine Height	34"
Machine Length	43"
Machine Width	33"
Shipping Weight	650 Lbs.
Lining: 90 Durometer	5/8 "
Input Voltage	110/1/60
Drive Unit: 1570 lbs. Force	1800 Rpm
Specifications subject to change	

OPTIONAL EQUIPMENT and SUPPLIES

▪ ST15FS Filtration System ▪ Includes Tank with Filtration Bags & Pump.



▪ TUB DIVIDER ▪ Bolt in Divider allows different parts to be run at one time and prevents parts from contact with each other



▪ Media and Compound Starter Kit for Steel Parts ▪ Includes load of media & 5 Gallon of Compound



▪ Media and Compound Starter Kit for Aluminum Parts ▪ Includes load of media & 5 Gallon of Compound



▪ Automatic Premixing Compound System ▪



AVAILABE IN OTHER SIZES

UM Abrasives Inc.  
831 Trent St  
Kennedale, TX. 76060  
(817) 572-1344  
[sales@umabrasives.com](mailto:sales@umabrasives.com)